

and installation failures and protects the system. Operations can be adjusted for all types of jar/bottle

and film. APACK will help you with procuring films.

AUTOSEAL

TECHNICAL SPECIFICATIONS

ENERGY	400V, 50-60Hz, 3/N/PE
POWER	6kW max
COMPRESSED AIR	6 bar Homogenedus-Dry Air
COMPRESSED AIR USE	40 Nl/cycle
CAPACITY	5-7 cycle/min
CONTROL SYSTEM	Omron 7" Touchscreen PLC
DIMENSIONS (W/L/H)mm.	850x2900x1700
WEIGHT	400 kg.
FILM WIDTH	230 mm
FILM REEL DIAMETER	76 mm
SEALING SURFACE	2 mm min





the AUTOSEAL series includes production lines which meet all your sealing needs for PET/PE jars/bottles of any size and various mouth diameters with fully automatic systems.





apack

FULL MEMBER OF THE TURKISH PACKAGING MACHINE PRODUCERS ASSOCIATION. MEMBER OF **EHEDG** (EUROPEAN HYGIENIC ENGINEERING

AND DESIGN GROUP).

PACKAGING TECHNOLOGIES

– APACK AMBALAJ MAKİNE SANAYİ TİCARET LTD. ŞTİ. Ferhatpaşa Mah. 22. Sok. No: 43 34888 Ataşehir İstanbul / Türkiye

T: +90 216 661 33 71 | M: +90 530 265 04 00 +90 216 661 26 69 www.apack.com.tr

+90 216 661 60 13 | info@apack.com.tr F: +90 216 661 33 70 | export@apack.com.tr Dealer:

@Fully Automatic Jar - Bottle Sealer

AUTOSEAL JS 230

PACKAGING